



材料名称	LDPE	东莞市凯腾塑胶电子有限公司 物质安全资料表 (MSDS)	文件编号	HBDG-01		
型号	5321		版次	A	页码	1-1
制定部门	品质部		制作	审核	批准	
日期	2008-1-1					

韩化化学公司
HANWHA CHEMICAL CORPORATION

项目/Items	材料安全资/MSDS (Material Datas System)	
产品厂商资料 Intormation supplier	物品名称/Product name	低密度聚乙烯/LDPE (LOWDINSITY POLYETHYLENE)
	物品编号/Product NO	LDPE5321
	供应商名称/Supplier	HANWHA CHEMICAL CORPORATION
	供应商地址/Adress	I JANGK YO DONG GU SEOUL KOREA
	供应商电话/Telephone	02-729-1282
成份辨识资料 Composition&informati cn noingredients	结构 CONSTRUCTION	名称NAME POLYOLEFINS聚乙烯 化学分子式FORMULA $[CH_2-CH_2]_n$
	CAS. NO.	09002-88-4
	沸点Boiling point (F)	N.A.
物理及化学性质	水汽密度Vapor Presure (mmhg)	N.A.
	空气密度Vapor density (AIR1)	N.A.
	水溶Solubility in Water	忽略Negligible
	外观Appearance	Odor 气味精可以忽略 Solid Pellet-Negligible Odor
	蒸发速率Evaporation Rate	N.A.
危害辨识资料 Ha/arc's indentification	健康危害/Harm to health	None
	环境影响 Harm to environment	环保产品. 低铅低镉 (<2PPM依EN1122) 兼 (<2PPM依EPA3052) 六价铬 (<2PPM依EPA3060A; 1996&EPA7196A; 1992)
	物理及化学性危害 Physical&chemical hazards	不可长时间与皮肤接触, 可能导致皮肤过敏 Can't be long-playing to contact the skin my cause the skin allstgic
	特殊危害ad hoc harm	None
	主要症状Symptoms	误食后引发呕吐, 腹胀现象/Vomitting, Windy or other
	救治措施 first-aid miasures	若吸入熔聚乙烯溢出气体, 将患者移至通风处, 立即送医 若眼睛接触到胶粒或粉末, 以大量清水冲洗至少15分钟并送医
灭火措施 Ffirehting measures	适用灭火剂/Suitable	水, 泡沫, 干粉/Water, Fog, Foam of dry chemicals
	灭火剂造成危害/ Flammability Classification	None
	特殊灭火程式 Special fire fighting procedures	消防员戴防护口罩避免吸入剂烟和臭气 firefighters should ewar self-contained breathing apparatus to prevent inhalation of smoke and fumes
泄露处理方法 deal wath way	个人注意事项/advort individua	若塑胶料或粉末残留在地面上, 可能会导致人员滑到./Stip
	环境注意事项/ advort circumstance	为防止鸟类或鱼类在排水系统摄食, 须彻底回收./callback
储运材料 skirage&transport information	储存要求/ Storage regulations	存防尘服清扫溢出材料的场地 leave in sb'S care shady and cool and no beacon
	搬运中装箱中材料的溢出/ Step to be taken in casematerial material is released or spilled	穿防尘服清扫溢出材料的场地 sweep up and place in a closed containerwear a dust mask if dust is

审核: 

制定: 